



1631

1631
1632
1633

BEAM POWER AMPLIFIER

For applications critical as to uniformity of characteristics

Heater	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.45	amp.
Plate Dissipation	16 max. watts	
<i>Other ratings, characteristics, dimensions, and socket connections for the 1631 are the same as those for Type 6L6. Typical operating data for the 6L6 also apply to the 1631 within the limitation of the maximum plate-dissipation rating.</i>		

1632

BEAM POWER AMPLIFIER

For applications critical as to uniformity of characteristics

Heater	Coated Unipotential Cathode	
Voltage	12.6	a-c or d-c volts
Current	0.6	amp.
Plate Voltage	117 max. volts	
Screen Voltage	117 max. volts	
Plate Dissipation	5.5 max. watts	
<i>Dimensions and socket connections for the 1632 are the same as for Type 25L6. Typical operating data for the 1632 are the same within its plate voltage and dissipation limitations as for the 25L6.</i>		

1633

TWIN-TRIODE AMPLIFIER

For applications critical as to matching of the two triode units

Heater	Coated Unipotential Cathode		
Voltage	25	a-c or d-c volts	
Current	0.15	amp.	
Direct Interelectrode Capacitances (Approx.): ^o			
	<u>Triode Unit T₁</u>	<u>Triode Unit T₂</u>	
Grid to Plate	3.6	3.6	μmf
Grid to Cathode	3.0	2.8	μmf
Plate to Cathode	0.8	1.2	μmf
Maximum Overall Length			3-5/16"
Maximum Seated Height			2-3/4"
Maximum Diameter			1-5/16"
Bulb			T-9
Base	Intermediate Shell Octal 8-Pin		
Pin 1 - Grid T ₂			Pin 5 - Plate T ₁
Pin 2 - Plate T ₂			Pin 6 - Cathode T ₁
Pin 3 - Cathode T ₂			Pin 7 - Heater
Pin 4 - Grid T ₁			Pin 8 - Heater
Mounting Position			Any



BOTTOM VIEW (8BD)

For convenience, one triode unit is identified as T₁; the other as T₂.

^o See next page.

Nov. 15, 1945

1633
1634



1633

TWIN-TRIODE AMPLIFIER

(continued from preceding page)

Maximum And Minimum Ratings Are Design-Center Values

AMPLIFIER - Each Unit

Plate Voltage	300 max. volts
Grid Voltage	0 min. volts
Cathode Current	20 max. ma.
Plate Dissipation	2.5 max. watts
D-C Heater-Cathode Potential	90 max. volts
<i>Characteristics - Class A₁ Amplifier:</i>	
Plate Voltage	250 volts
Grid Voltage*	-8 volts
Amplification Factor	18
Plate Resistance	6900 ohms
Transconductance	2600 μ hos
Plate Current	11.5 ma.

⁰ With no external shield.

[#] The d-c resistance in the grid circuit should not exceed 1.0 megohm under maximum rated conditions per unit.

Curves for Type 1633 are the same as for the 6J5, and 6SN7-GT.

1634

TWIN-TRIODE AMPLIFIER

For applications critical as to matching of the two triode units

Maximum ratings, characteristics, dimensions, and socket connections for the 1634 are the same as for Type 12SC7.