

4AU6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4AU6 is the same as the 6AU6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

| | | |
|---|---------------|-------|
| Current | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at heater amperes = 0.450 | 4.2 | volts |
| Warm-up time (Average) | 11 | sec |

4AV6

Twin Diode—High-Mu Triode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4AV6 is the same as the 6AV6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

| | | |
|---|---------------|-------|
| Current | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at heater amperes = 0.450 | 4.2 | volts |
| Warm-up time (Average) | 11 | sec |

4BC5

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BC5 is the same as the 6BC5 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

| | | |
|---|-----------------------|-------|
| Current | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at heater amperes = 0.450 | 4.2 | volts |
| Warm-up time (Average) | 11 | sec |
| Peak heater-cathode voltage: | | |
| Heater negative with respect to cathode | 200 max. | volts |
| Heater positive with respect to cathode | 200 ^a max. | volts |

^a The dc component must not exceed 100 volts.

