



6CS7

6CS7

MEDIUM-MU DUAL TRIODE With Dissimilar Units

9-PIN MINIATURE TYPE

Intended for use in equipment having
series heater-string arrangement

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage.	6.3	ac or dc volts
Current.	0.6	amp
Warm-up time (Average).	11	sec

For definition of heater warm-up time and method of determining it, see sheet HEATER WARM-UP TIME MEASUREMENT at front of this Section.

Direct Interelectrode Capacitances (Approx.):^o

	Unit No. 1 Oscillator	Unit No. 2 Amplifier	
Grid to plate.	2.6	2.6	$\mu\mu\text{f}$
Grid to cathode and heater..	1.8	3	$\mu\mu\text{f}$
Plate to cathode and heater.	0.5	0.5	$\mu\mu\text{f}$

Characteristics, Class A₁ Amplifier:

	Unit No. 1 Oscillator	Unit No. 2 Amplifier	
Plate Voltage.	250	250	volts
Grid Voltage	-8.5	-10.5	volts
Amplification Factor	17	15.5	
Plate Resistance (Approx.)	7700	3450	ohms
Transconductance	2200	4500	μmhos
Plate Current.	10.5	19	ma
Plate Current for grid volts = -16.	-	3	ma
Grid Voltage (Approx.) for plate current of:			
10 microamperes.	-24	-	volts
50 microamperes.	-	-22	volts

Mechanical:

Operating Position	Any
Maximum Overall Length	2-5/8"
Maximum Seated Length.	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip)	2" \pm 3/32"
Diameter	0.750" to 0.875"
Dimensional Outline.	See General Section
Bulb	T6-1/2

^o: See next page.

6CS7




6CS7

MEDIUM-MU DUAL TRIODE
With Dissimilar Units

Base Small-Button Noval 9-Pin (JETEC No. E9-1)
 Basing Designation for BOTTOM VIEW 9EF

Pin 1 - Plate of Unit No.2
 Pin 2 - No Connection
 Pin 3 - Grid of Unit No.2
 Pin 4 - Heater
 Pin 5 - Heater



Pin 6 - Plate of Unit No.1
 Pin 7 - Grid of Unit No.1
 Pin 8 - Cathode of Unit No.1
 Pin 9 - Cathode of Unit No.2

VERTICAL-DEFLECTION OSCILLATOR

Values are for Unit No. 1

Maximum Ratings, Design-Center Values:

For operation in a 525-line, 30-frame system[□]

DC PLATE VOLTAGE	500 max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE	400 max.	volts
CATHODE CURRENT:		
Peak	70 max.	ma
DC	20 max.	ma
PLATE DISSIPATION	1.25 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 [▲] max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance	2.2 max.	megohms
-----------------------------------	----------	---------

VERTICAL-DEFLECTION AMPLIFIER

Values are for Unit No. 2

Maximum Ratings, Design-Center Values Except as Noted:

For operation in a 525-line, 30-frame system[□]

DC PLATE VOLTAGE	500 max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE [#]		
(Absolute maximum)	2200 [■] max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE	250 max.	volts
CATHODE CURRENT:		
Peak	105 max.	ma
DC	30 max.	ma
PLATE DISSIPATION	6.5 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 [▲] max.	volts

□, ▲, #, ■: See next page.



6CS7

MEDIUM-MU DUAL TRIODE
With Dissimilar Units

6CS7

Maximum Circuit Values:

Grid-Circuit Resistance. 2.2 max. megohms

□ As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

▲ The dc component must not exceed 100 volts.

* This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.

■ Under no circumstances should this absolute value be exceeded.

○ without external shield.