



3C23

3C23

GAS-AND-MERCURY-VAPOR THYRATRON

NEGATIVE-CONTROL TRIODE TYPE

GENERAL DATA

Electrical:

Filament, Coated:

Voltage 2.5 ± 5% ac or dc volts ←

Current at 2.5 volts. 7 amp ←

Minimum heating time prior to
tube conduction 15 sec ←Direct Interelectrode Capacitance (Approx.):^o

Grid to anode 1.8 μuf ←

Ionization Time (Approx.):

For conditions: dc anode volts = 100,
peak grid volts = +30, and peak
anode amperes = 6 3 μsec ←

Deionization Time (Approx.):

For conditions: dc anode volts = 120,
dc grid-supply volts = -20, grid re-
sistor (ohms) = 10000, and dc
anode amperes = 1.5 360 μsec ←For conditions: dc anode volts = 120,
dc grid-supply volts = -500, grid re-
sistor (ohms) = 100000, and dc
anode amperes = 1.5 60 μsec ←

Anode Voltage Drop (Approx.). 15 volts ←

Mechanical:

Mounting Position Vertical, base down

Maximum Overall Length. 6-1/8"

Seated Length 5-1/4" ± 1/4"

Maximum Diameter 2-1/16"

Cooling Natural circulation of air around tube

Weight (Approx.) 3 oz ←


Bulb. ST-16 ←

Cap Medium (JETEC No.C1-5) ←

Base. Medium-Shell Small 4-Pin
with Bayonet (JETEC No.A4-10) ←

Basing Designation for BOTTOM VIEW 3G ←

Pin 1 - Filament



Pin 4 - Filament

Pin 2 - No Connection

Cap - Anode

Pin 3 - Grid

CONTROL SERVICE

Maximum Ratings, Absolute Values: For supply frequency up to 400 cps

Operating Condensed-Mercury
Temperature Range

-40° to +100°C -40° to +80°C

PEAK ANODE VOLTAGE:

Forward 200 max. 1250 max. volts ←

Inverse 200 max. 1250 max. volts ←

^o without external shield.

← Indicates a change.

3C23



3C23

GAS-AND-MERCURY-VAPOR THYRATRON

Operating Condensed-Mercury
Temperature Range

-40° to +100°C -40° to +80°C

GRID VOLTAGE:

Peak or DC, before tube conduction -500 max. -500 max. volts

Average^a, during tube conduction -10 max. -10 max. volts

ANODE CURRENT:

Peak. 6 max. 6 max. amp

Average^b. 1.5 max. 1.5 max. amp

Fault, for duration of 0.1 second max. 120 max. 120 max. amp


GRID CURRENT:

Average^c. +0.01 max. +0.01 max. amp

^a Averaged over one conducting period.

^b Averaged over any interval of 5 seconds maximum.

^c Averaged over period of grid conduction.



92CS-6745R2



3C23

3C23

GAS - AND - MERCURY-VAPOR THYRATRON

OPERATIONAL RANGE
OF CRITICAL GRID VOLTAGE

RANGE IS FOR CONDITIONS WHERE:
 $E_f = 2.5$ VOLTS AC $\pm 5\%$; CIRCUIT RE-
TURNS TO CENTER TAP OF FILAMENT
TRANSFORMER. THE RANGE INCLUDES
INITIAL AND LIFE VARIATIONS OF IN-
DIVIDUAL TUBES. GRID RESISTOR=0
TO 100000 OHMS. CONDENSED-MERCURY
TEMPERATURE=-40°C TO +80°C.

