



6B4-G

6B4-G
6B5

POWER AMPLIFIER TRIODE

Filament	Coated	
Voltage	6.3	a-c or d-c volts
Current	1.0	amp.
Maximum Overall Length		5-5/16"
Maximum Seated Height		4-3/4"
Maximum Diameter		2-1/16"
Bulb		ST-16
Base		Medium Shell Octal 8-Pin
Pin 1 - No Connection		Pin 5 - Grid
Pin 2 - Filament		Pin 6 - No Connection
Pin 3 - Plate		Pin 7 - Filament
Pin 4 - No Connection		Pin 8 - No Connection
Mounting Position		Any

BOTTOM VIEW (G-5S_B)

Maximum Ratings, and Typical Operating Conditions for the 6B4-G are the same as for the Type 6A3.

Curves for the 6B4-G are essentially the same as those shown for Type 2A3.

6B5



DIRECT-COUPLED POWER AMPLIFIER

Heater	Coated Unipotential Cathode	
Voltage	6.3	a-c or d-c volts
Current	0.8	amp.
Maximum Overall Length		4-11/16"
Maximum Seated Height		4-1/16"
Maximum Diameter		1-13/16"
Bulb		ST-14
Base		Medium 6-Pin
Pin 1 - Heater		Pin 4 - Input-Triode
Pin 2 - Output-Triode		Grid
Pin 3 - Input-Triode		Pin 5 - Cathode
Pin 4 - Heater		Pin 6 - Heater
Mounting Position		Any

BOTTOM VIEW (6AS)

For additional data, refer to Type 6N6-G.

←Indicates a change.

May 1, 1941

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

TENTATIVE DATA