



25Y5

25Y5



HIGH-VACUUM RECTIFIER-DOUBLER

Heater	Coated Unipotential Cathodes	
Voltage	25	a-c or d-c volts
Current	0.3	amp.
Maximum Overall Length		4-3/16"
Maximum Seated Height		3-9/16"
Maximum Diameter		1-9/16"
Bulb		ST-12
Base		Small 6-Pin
Pin 1 - Heater		Pin 4 - Cathode #1
Pin 2 - Plate #2		Pin 5 - Plate #1
Pin 3 - Cathode #2		Pin 6 - Heater
Mounting Position		Any

BOTTOM VIEW (6E)

RECTIFIER

Peak Inverse Voltage		700 max. volts
Peak Plate Current per Plate		450 max. ma.
D-C Heater-Cathode Potential		350 max. volts
<i>Operation as Half-Wave Rectifier with Condenser-Input Filter:*</i>		
A-C Plate Volt. per Plate (RMS)	150	235 max. volts
Total Effective Plate-Supply Impedance per Plate [▲]	0	0 ohms
D-C Output Current per Plate	75 max.	75 max. ma.

* In half-wave rectifier service, the two units may be used separately or in parallel.

▲ When a filter-input condenser larger than 40 μf is used, it may be necessary to use more plate-supply impedance than the minimum value shown to limit the peak plate current to the rated value.

The curve under type 25Z6 also applies to the 25Y5.

May 1, 1941

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

TENTATIVE DATA